

**REFRIGERATED CABINETS GN2/1 VENTILATED - M-GNH610TN-FC**

SKU: M-GNH610TN-FC



**DATI TECNICI**

|  |                               |
|--|-------------------------------|
| <b>OPERATING TEMPERATURE</b>               | <u>+0°C / +8°C</u>            |
| <b>EXTERNAL DIMENSIONS</b>                 | <u>726 x 864 x 2150(h) mm</u> |
| <b>INTERNAL DIMENSIONS (l x l x h -mm)</b> | <u>566 x 714 x 1500(h) mm</u> |
| <b>CAPACITY (L)</b>                        | <u>605</u>                    |
| <b>MAX. OPERATING TEMPERATURE</b>          | <u>38°C / 70%HR</u>           |
| <b>TYPE OF COOLING</b>                     | <u>ventilated</u>             |
| <b>DEFROSTING TYPE</b>                     | <u>automatico</u>             |
| <b>TYPE OF COOLING GAS</b>                 | <u>R290</u>                   |
| <b>CONDENSED WATER EVAPORATION</b>         | <u>automatic</u>              |
| <b>TEMPERATURE CONTROL</b>                 | <u>electronic</u>             |
| <b>INSULATION (mm)</b>                     | <u>80</u>                     |
| <b>POWER CONSUMPTION (W)</b>               | <u>167</u>                    |

|                              |  |
|------------------------------|--|
| <b>VOLTAGE</b>               | <u>220V-240V / 50Hz</u>                    |
| <b>CONSTRUCTION MATERIAL</b> | <u>stainless steel</u>                     |
| <b>DOOR REVERSING</b>        | <u>yes</u>                                 |
| <b>INTERIOR LIGHT</b>        | <u>led</u>                                 |
| <b>SUPPLIED ACCESSORIES</b>  | <u>3 grids / GN2/1 3 pairs of slides /</u> |
| <b>ENERGY CLASS</b>          | <u>A</u>                                   |
| <b>PESO NETTO (Kg)</b>       | 122  |
| <b>PESO LORDO (Kg)</b>       | 138  |
| <b>DIMENSIONI IMBALLO</b>    | 756 x 890 x 2190(h) mm                     |

#### NEW MODEL MONOBLOCK

The refrigerated cabinets of the GNH line are made of stainless steel - GN 2/1 grids on standard guides - 80 mm insulation - Monobloc refrigerating unit - plug-in system refrigerating unit featuring easy and immediate installation or eventual removal/replacement - quieter motor - Monobloc protected by stainless steel sheet.

